



SUPRO[®]
>>BOX

R SERIES

TRANSPORTATION AND STORAGE CASES

nbcssystem.it



Suprobox cases have been made to withstand the toughest environmental and climatic conditions.

The case is manufactured as a solid uniform structure which makes it extra resistant to impact and vibration enabling the case to be handled and transported in extreme situations.

The polymer raw material resin is UV resistant and is specifically designed to function in extreme temperatures and under solar load.

Ideal for electronics, memory storage equipment, servers, lab and testing equipment, medical equipment, aerospace equipment, broadcasting equipment, meteorological equipment, flight simulators, satellite communications, radars and mobile military equipment.

R SERIES 194 different sizes

RACK CASES 24 different sizes

With over 200 sizes SUPROBOX offer one of the widest selections available in the market. Once placed in a Suprobox case, your delicate equipment and instruments are transported and used under complete protection from shock, vibration, moisture and impact. Your cases come furnished with the appropriate grade foam and/or shock mounting equipment in line with your special project requirements.

- Ruggedized case body made from impact resistant PE material
- Easy grip ruggedized stainless steel handles
- Stainless Steel, heavy duty catches
- Automatic pressure relief valve (standard)
- Waterproof silicone seal between body and lid
- Extra resistant to impact & vibration
- UV resistant
- Made to withstand extreme temperatures & solar load
- Optional rugged edge castors
- Custom internals available
- Color options
- Multibrix® stacking system (straight or cross stacking of same or different size cases)
- MIL-STD 810 G
- Dust and Water Protection rated IP 65/IP 67



Contents

Suprobox R Series Technical Specifications.....	02
Suprobox R Series Dimensions	26
Custom Solutions.....	30
Options.....	31
Suprobox Rack Series Technical Specifications.....	32
Suprobox Rack Cases.....	36
Suprobox Rack Series Dimensions.....	37
Multibrix.....	39
Tests.....	41



SUPROBOX R SERIES

TECHNICAL SPECIFICATIONS



Easy grip ruggedized stainless steel handles.

Multibrix stacking system.

Breather valve (Optional) maintains pressure balance

Stainless Steel, heavy duty catches are larger than standard products available on the market.

76mm rigid edge casters enable the case to be mobilized by lifting the handle. Built in edge casters are compatible with the stacking feature.

Waterproof silicone seal between base and lid.

Manufactured as a solid uniform structure which makes it extra resistant to impact & vibration.

UV resistant made to withstand extreme temperatures & solar load.





3030-3010



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
3030-3010	300	300	400	210	210	350	280+70	2	4,2	-----

4040-3010



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
4040-3010	400	400	400	310	310	350	280+70	2	6,3	-----

5050-3010



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
5050-3010	500	500	400	410	410	350	280+70	2	8,0	-----

6050-2010



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
6050-2010	600	500	300	510	410	250	180+70	2	8,7	-----

6050-3010



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
6050-3010	600	500	400	510	410	350	280+70	2	9,4	-----

6050-5010



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
6050-5010	600	500	600	510	410	550	480+70	2	12,0	-----

6050-2043



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
6050-2043	600	500	630	510	410	580	180+400	4	14,1	-----

6050-3043



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
6050-3043	600	500	730	510	410	680	280+400	4	14,9	-----

6050-5043



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
6050-5043	600	500	930	510	410	880	480+400	4	17,5	-----

8040-3010 8040-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8040-3010	800	400	400	710	310	350	280+70	2	10,1	-----
8040-3010T	800	400	400	710	310	350	280+70	2	10,7	Wheels

8050-3010 8050-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8050-3010	800	500	400	710	410	350	280+70	2	11,5	-----
8050-3010T	800	500	400	710	410	350	280+70	2	12,1	Wheels

8060-2010 8060-2010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-2010	800	600	300	710	510	250	180+70	4	13,6	-----
8060-2010T	800	600	300	710	510	250	180+70	4	14,2	Wheels

8060-1123



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-1123	800	600	340	710	510	290	90+200	4	14,8	-----

8060-3010 8060-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-3010	800	600	400	710	510	350	280+70	4	14,8	-----
8060-3010T	800	600	400	710	510	350	280+70	4	15,4	Wheels



8060-2023 8060-2023T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-2023	800	600	430	710	510	380	180+200	4	16,2	-----
8060-2023T	800	600	430	710	510	380	180+200	4	16,8	Wheels

8060-4010 8060-4010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-4010	800	600	500	710	510	450	380+70	4	16,6	-----
8060-4010T	800	600	500	710	510	450	380+70	4	17,2	Wheels

8060-3023 8060-3023T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-3023	800	600	530	710	510	480	280+200	4	17,4	-----
8060-3023T	800	600	530	710	510	480	280+200	4	18,0	Wheels

8060-1143



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-1143	800	600	540	710	510	490	90+400	4	18,3	-----

8060-5010 8060-5010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-5010	800	600	600	710	510	550	480+70	4	17,5	-----
8060-5010T	800	600	600	710	510	550	480+70	4	18,1	Wheels

8060-2043 8060-2043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-2043	800	600	630	710	510	580	180+400	8	20,9	-----
8060-2043T	800	600	630	710	510	580	180+400	8	21,5	Wheels

8060-4023 8060-4023T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-4023	800	600	630	710	510	580	380+200	4	19,2	-----
8060-4023T	800	600	630	710	510	580	380+200	4	19,8	Wheels

8060-3043 8060-3043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-3043	800	600	730	710	510	680	280+400	8	22,1	-----
8060-3043T	800	600	730	710	510	680	280+400	8	22,7	Wheels

8060-5023 8060-5023T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-5023	800	600	730	710	510	680	480+200	4	20,2	-----
8060-5023T	800	600	730	710	510	680	480+200	4	20,8	Wheels

8060-4043 8060-4043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-4043	800	600	830	710	510	780	380+400	8	23,9	-----
8060-4043T	800	600	830	710	510	780	380+400	8	24,5	Wheels

8060-5043 8060-5043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8060-5043	800	600	930	710	510	880	480+400	8	24,9	-----
8060-5043T	800	600	930	710	510	880	480+400	8	25,5	Wheels

8070-2010 8070-2010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8070-2010	800	700	300	710	610	250	180+70	4	14,9	-----
8070-2010T	800	700	300	710	610	250	180+70	4	15,5	Wheels

8070-2022 8070-2022T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8070-2022	800	700	420	710	610	370	180+190	4	17,0	-----
8070-2022T	800	700	420	710	610	370	180+190	4	17,6	Wheels

8070-4010 8070-4010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8070-4010	800	700	500	710	610	450	380+70	4	18,0	-----
8070-4010T	800	700	500	710	610	450	380+70	4	18,6	Wheels

8070-2042 8070-2042T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8070-2042	800	700	620	710	610	570	180+390	8	21,4	-----
8070-2042T	800	700	620	710	610	570	180+390	8	22,0	Wheels

8070-4022 8070-4022T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8070-4022	800	700	620	710	610	570	380+190	4	20,1	-----
8070-4022T	800	700	620	710	610	570	380+190	4	20,7	Wheels

8070-6010 8070-6010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8070-6010	800	700	700	710	610	650	580+70	4	21,5	-----
8070-6010T	800	700	700	710	610	650	580+70	4	22,1	Wheels

8070-2062 8070-2062T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8070-2062	800	700	820	710	610	770	180+590	8	24,8	-----
8070-2062T	800	700	820	710	610	770	180+590	8	25,4	Wheels

8070-4042 8070-4042T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8070-4042	800	700	820	710	610	770	380+390	8	24,5	-----
8070-4042T	800	700	820	710	610	770	380+390	8	25,1	Wheels

8070-6022 8070-6022T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8070-6022	800	700	820	710	610	770	580+190	4	23,6	-----
8070-6022T	800	700	820	710	610	770	580+190	4	24,2	Wheels

8070-4062 8070-4062T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8070-4062	800	700	1020	710	610	970	380+590	8	27,8	-----
8070-4062T	800	700	1020	710	610	970	380+590	8	28,4	Wheels

8070-6042 8070-6042T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8070-6042	800	700	1020	710	610	970	580+390	8	28,0	-----
8070-6042T	800	700	1020	710	610	970	580+390	8	28,6	Wheels

8070-6062 8070-6062T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
8070-6062	800	700	1220	710	610	1170	580+590	8	31,3	-----
8070-6062T	800	700	1220	710	610	1170	580+590	8	31,9	Wheels

9040-3010 9040-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9040-3010	900	400	400	810	310	350	280+70	2	11,2	-----
9040-3010T	900	400	400	810	310	350	280+70	2	11,8	Wheels

9050-3010 9050-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9050-3010	900	500	400	810	410	350	280+70	2	12,5	-----
9050-3010T	900	500	400	810	410	350	280+70	2	13,1	Wheels

9050-3010TTEP



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9050-3010TTEP	900	500	400	810	410	350	280+70	2	15,6	Wheels+Tepsi x 2

9050-4010 9050-4010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9050-4010	900	500	500	810	410	450	380+70	2	14,3	-----
9050-4010T	900	500	500	810	410	450	380+70	2	14,9	Wheels

9050-4010TTEP



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9050-4010TTEP	900	500	500	810	410	450	380+70	2	17,4	Wheels+Tepsi x 2

9060-2010 9060-2010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9060-2010	900	600	300	810	510	250	180+70	4	14,6	-----
9060-2010T	900	600	300	810	510	250	180+70	4	15,2	Wheels

9060-3010 9060-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9060-3010	900	600	400	810	510	350	280+70	4	15,4	-----
9060-3010T	900	600	400	810	510	350	280+70	4	16,0	Wheels



9060-4010 9060-4010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9060-4010	900	600	500	810	510	450	380+70	4	17,9	-----
9060-4010T	900	600	500	810	510	450	380+70	4	18,5	Wheels

9060-5010 9060-5010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9060-5010	900	600	600	810	510	550	480+70	4	18,2	-----
9060-5010T	900	600	600	810	510	550	480+70	4	18,8	Wheels

9060-2043 9060-2043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9060-2043	900	600	630	810	510	580	180+400	8	22,7	-----
9060-2043T	900	600	630	810	510	580	180+400	8	23,3	Wheels

9060-3043 9060-3043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9060-3043	900	600	730	810	510	680	280+400	8	23,3	-----
9060-3043T	900	600	730	810	510	680	280+400	8	23,9	Wheels

9060-4043 9060-4043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9060-4043	900	600	830	810	510	780	380+400	8	26,0	-----
9060-4043T	900	600	830	810	510	780	380+400	8	26,6	Wheels

9060-5043 9060-5043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9060-5043	900	600	930	810	510	880	480+400	8	26,3	-----
9060-5043T	900	600	930	810	510	880	480+400	8	26,9	Wheels

9070-2010 9070-2010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9070-2010	900	700	300	810	610	250	180+70	4	16,2	-----
9070-2010T	900	700	300	810	610	250	180+70	4	16,8	Wheels

9070-2022 9070-2022T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9070-2022	900	700	420	810	610	370	180+190	4	18,6	-----
9070-2022T	900	700	420	810	610	370	180+190	4	19,2	Wheels

9070-4010 9070-4010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9070-4010	900	700	500	810	610	450	380+70	4	19,7	-----
9070-4010T	900	700	500	810	610	450	380+70	4	20,3	Wheels

9070-2042 9070-2042T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9070-2042	900	700	620	810	610	570	180+390	8	23,2	-----
9070-2042T	900	700	620	810	610	570	180+390	8	23,8	Wheels

9070-4022 9070-4022T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9070-4022	900	700	620	810	610	570	380+190	4	22,1	-----
9070-4022T	900	700	620	810	610	570	380+190	4	22,7	Wheels

9070-6010 9070-6010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9070-6010	900	700	700	810	610	650	580+70	4	23,1	-----
9070-6010T	900	700	700	810	610	650	580+70	4	23,7	Wheels

9070-2062 9070-2062T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9070-2062	900	700	820	810	610	770	180+590	8	26,7	-----
9070-2062T	900	700	820	810	610	770	180+590	8	27,3	Wheels

9070-4042 9070-4042T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9070-4042	900	700	820	810	610	770	380+390	8	26,7	-----
9070-4042T	900	700	820	810	610	770	380+390	8	27,3	Wheels

9070-6022 9070-6022T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9070-6022	900	700	820	810	610	770	580+190	4	25,5	-----
9070-6022T	900	700	820	810	610	770	580+190	4	26,1	Wheels

9070-4062 9070-4062T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9070-4062	900	700	1020	810	610	970	380+590	8	30,2	-----
9070-4062T	900	700	1020	810	610	970	380+590	8	30,8	Wheels

9070-6042 9070-6042T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9070-6042	900	700	1020	810	610	970	580+390	8	30,1	-----
9070-6042T	900	700	1020	810	610	970	580+390	8	30,7	Wheels

9070-6062 9070-6062T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
9070-6062	900	700	1220	810	610	1170	580+590	8	33,6	-----
9070-6062T	900	700	1220	810	610	1170	580+590	8	34,2	Wheels

10040-3010 10040-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
10040-3010	1000	400	400	910	310	350	280+70	2	12,3	-----
10040-3010T	1000	400	400	910	310	350	280+70	2	12,9	Wheels

10050-3010 10050-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
10050-3010	1000	500	400	910	410	350	280+70	2	13,7	-----
10050-3010T	1000	500	400	910	410	350	280+70	2	14,3	Wheels

10060-2010 10060-2010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
10060-2010	1000	600	300	910	510	250	180+70	4	16,0	-----
10060-2010T	1000	600	300	910	510	250	180+70	4	16,6	Wheels

10060-3010 10060-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
10060-3010	1000	600	400	910	510	350	280+70	4	17,2	-----
10060-3010T	1000	600	400	910	510	350	280+70	4	17,8	Wheels

10060-4010 10060-4010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
10060-4010	1000	600	500	910	510	450	380+70	4	19,5	-----
10060-4010T	1000	600	500	910	510	450	380+70	4	20,1	Wheels

10060-5010 10060-5010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
10060-5010	1000	600	600	910	510	550	480+70	4	20,4	-----
10060-5010T	1000	600	600	910	510	550	480+70	4	21,0	Wheels

10060-2043 10060-2043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
10060-2043	1000	600	630	910	510	580	180+400	8	24,2	-----
10060-2043T	1000	600	630	910	510	580	180+400	8	24,8	Wheels

10060-3043 10060-3043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
10060-3043	1000	600	730	910	510	680	280+400	8	25,4	-----
10060-3043T	1000	600	730	910	510	680	280+400	8	26,0	Wheels

10060-4043 10060-4043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
10060-4043	1000	600	830	910	510	780	380+400	8	27,7	-----
10060-4043T	1000	600	830	910	510	780	380+400	8	28,3	Wheels

10060-5043 10060-5043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
10060-5043	1000	600	930	910	510	880	480+400	8	28,4	-----
10060-5043T	1000	600	930	910	510	880	480+400	8	29,0	Wheels

10090-3013 10090-3013T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
10090-3013	1000	900	430	910	810	350	265+85	4	29,9	-----
10090-3013T	1000	900	430	910	810	350	265+85	4	30,5	Wheels

100100-3013 100100-3013T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
100100-3013	1000	1000	430	910	910	350	265+85	4	32,4	-----
100100-3013T	1000	1000	430	910	910	350	265+85	4	33,0	Wheels



11040-3010 11040-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
11040-3010	1100	400	400	1010	310	350	280+70	2	13,4	-----
11040-3010T	1100	400	400	1010	310	350	280+70	2	14,0	Wheels

11050-3010 11050-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
11050-3010	1100	500	400	1010	410	350	280+70	2	14,8	-----
11050-3010T	1100	500	400	1010	410	350	280+70	2	15,4	Wheels

11070-2015T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
11070-2015T	1100	700	350	1010	610	300	180+120	4	21,0	Wheels

11070-2025T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
11070-2025T	1100	700	450	1010	610	400	180+220	8	23,2	Wheels

11070-3615T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
11070-3615T	1100	700	510	1010	610	460	340+120	4	24,2	Wheels

11070-3625T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
11070-3625T	1100	700	610	1010	610	560	340+220	8	26,9	Wheels

11070-5215T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
11070-5215T	1100	700	670	1010	610	620	500+120	4	28,2	Wheels

11070-5225T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
11070-5225T	1100	700	770	1010	610	720	500+220	8	30,9	Wheels

12040-3010 12040-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12040-3010	1200	400	400	1110	310	350	280+70	2	14,5	-----
12040-3010T	1200	400	400	1110	310	350	280+70	2	15,1	Wheels

12050-3010 12050-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12050-3010	1200	500	400	1110	410	350	280+70	2	15,9	-----
12050-3010T	1200	500	400	1110	410	350	280+70	2	16,5	Wheels

12060-2010 12060-2010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-2010	1200	600	300	1110	510	250	180+70	4	18,8	-----
12060-2010T	1200	600	300	1110	510	250	180+70	4	19,4	Wheels

12060-3010F



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-3010F	1200	600	400	1110	510	250	180+70	4	20,5	Forklift Skids

12060-3010 12060-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-3010	1200	600	400	1110	510	350	280+70	4	19,1	-----
12060-3010T	1200	600	400	1110	510	350	280+70	4	19,7	Wheels

12060-3710T6R- M4-M16



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-3710T6R-M4-M16	1200	600	470					4	33,5	Wheels

12060-4010F



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-4010F	1200	600	500	1110	510	350	280+70	4	22,5	Forklift Skids

12060-4010 12060-4010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-4010	1200	600	500	1110	510	450	380+70	4	22,9	-----
12060-4010T	1200	600	500	1110	510	450	380+70	4	23,5	Wheels

12060-5010F



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-5010F	1200	600	600	1110	510	450	380+70	4	24,4	Forklift Skids

12060-5010 12060-5010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-5010	1200	600	600	1110	510	550	480+70	4	23,1	-----
12060-5010T	1200	600	600	1110	510	550	480+70	4	23,7	Wheels

12060-6010F



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-6010F	1200	600	700	1110	510	550	480+70	4	26,4	Forklift Skids

12060-2043 12060-2043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-2043	1200	600	630	1110	510	580	180+400	8	27,8	-----
12060-2043T	1200	600	630	1110	510	580	180+400	8	28,4	Wheels

12060-3043F



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-3043F	1200	600	730	1110	510	580	180+400	8	29,5	Forklift Skids

12060-3043 12060-3043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-3043	1200	600	730	1110	510	680	280+400	8	28,1	-----
12060-3043T	1200	600	730	1110	510	680	280+400	8	28,7	Wheels

12060-4043F



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-4043F	1200	600	830	1110	510	680	280+400	8	31,5	Forklift Skids

12060-4043 12060-4043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-4043	1200	600	830	1110	510	780	380+400	8	31,9	-----
12060-4043T	1200	600	830	1110	510	780	380+400	8	32,5	Wheels

12060-5043F



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-5043F	1200	600	930	1110	510	780	380+400	8	33,4	Forklift Skids

12060-5043 12060-5043T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-5043	1200	600	930	1110	510	880	480+400	8	32,1	-----
12060-5043T	1200	600	930	1110	510	880	480+400	8	32,7	Wheels

12060-6043F



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12060-6043F	1200	600	1030	1110	510	880	480+400	8	35,4	Forklift Skids

12070-4010 12070-4010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12070-4010	1200	700	500	1110	610	450	380+70	4	24,9	-----
12070-4010T	1200	700	500	1110	610	450	380+70	4	25,5	Wheels

12070-6010 12070-6010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
12070-6010	1200	700	700	1110	610	650	580+70	4	32,5	-----
12070-6010T	1200	700	700	1110	610	650	580+70	4	33,1	Wheels

14040-3010 14040-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
14040-3010	1400	400	400	1310	310	350	280+70	2	16,4	-----
14040-3010T	1400	400	400	1310	310	350	280+70	2	17,0	Wheels

15060-3010 15060-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
15060-3010	1500	600	400	1410	510	350	280+70	4	24,5	-----
15060-3010T	1500	600	400	1410	510	350	280+70	4	25,1	Wheels

15060-4010 15060-4010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
15060-4010	1500	600	500	1410	510	450	380+70	4	26,8	-----
15060-4010T	1500	600	500	1410	510	450	380+70	4	27,4	Wheels

15060-5010 15060-5010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
15060-5010	1500	600	600	1410	510	550	480+70	4	29,2	-----
15060-5010T	1500	600	600	1410	510	550	480+70	4	29,8	Wheels

160125-5144F



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
160125-5144F	1600	1250	950	1510	1160	775	385+390	8	85,6	Forklift

17040-3010 17040-3010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
17040-3010	1700	400	400	1610	310	350	280+70	2	19,3	-----
17040-3010T	1700	400	400	1610	310	350	280+70	2	19,9	Wheels

18070-4010 18070-4010T



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
18070-4010	1800	700	500	1710	610	450	380+70	4	35,4	-----
18070-4010T	1800	700	500	1710	610	450	380+70	4	36,0	Wheels



21060-5010F



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
21060-5010F	2100	600	600	2010	510	445	375+70	4	39,7	Forklift Skids

22090-5852F



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
22090-5852F	2200	900	1100	2110	810	910	445+465	8	100,3	Forklift Skids

28090-5852F



CASE	EXTERIOR DIMENSIONS (mm)			INTERIOR DIMENSIONS (mm)				HANDLE (Pcs)	WEIGHT (Kg)	SPECIAL FEATURES
	Length	Width	Height	Length	Width	Height	Body+Lid			
28090-5852F	2800	900	1100	2710	810	910	445+465	8	123,2	Forklift Skids



R SERIES DIMENSIONS

CASE	EXTERIOR DIMENSIONS (mm)					INTERIOR DIMENSIONS (mm)					Handle (Pcs)	Weight (kg)	Special Features
	Length	Width	Height	Body Height	Lid Height	Length	Width	Height	Body Height	Lid Height			
3030-3010	300	300	400	300	100	210	210	350	280	70	2	4,2	-----
4040-3010	400	400	400	300	100	310	310	350	280	70	2	6,3	-----
5050-3010	500	500	400	300	100	410	410	350	280	70	2	8,0	-----
6050-2010	600	500	300	200	100	510	410	250	180	70	2	8,7	-----
6050-3010	600	500	400	300	100	510	410	350	280	70	2	9,4	-----
6050-5010	600	500	600	500	100	510	410	550	480	70	2	12,0	-----
6050-2043	600	500	630	200	430	510	410	580	180	400	4	14,1	-----
6050-3043	600	500	730	300	430	510	410	680	280	400	4	14,9	-----
6050-5043	600	500	930	500	430	510	410	880	480	400	4	17,5	-----
8040-3010	800	400	400	300	100	710	310	350	280	70	2	10,1	-----
8040-3010T	800	400	400	300	100	710	310	350	280	70	2	10,7	Wheels
8050-3010	800	500	400	300	100	710	410	350	280	70	2	11,5	-----
8050-3010T	800	500	400	300	100	710	410	350	280	70	2	12,1	Wheels
8060-2010	800	600	300	200	100	710	510	250	180	70	4	13,6	-----
8060-2010T	800	600	300	200	100	710	510	250	180	70	4	14,2	Wheels
8060-1123	800	600	340	110	230	710	510	290	90	200	4	14,8	-----
8060-3010	800	600	400	300	100	710	510	350	280	70	4	14,8	-----
8060-3010T	800	600	400	300	100	710	510	350	280	70	4	15,4	Wheels
8060-2023	800	600	430	200	230	710	510	380	180	200	4	16,2	-----
8060-2023T	800	600	430	200	230	710	510	380	180	200	4	16,8	Wheels
8060-4010	800	600	500	400	100	710	510	450	380	70	4	16,6	-----
8060-4010T	800	600	500	400	100	710	510	450	380	70	4	17,2	Wheels
8060-3023	800	600	530	300	230	710	510	480	280	200	4	17,4	-----
8060-3023T	800	600	530	300	230	710	510	480	280	200	4	18,0	Wheels
8060-1143	800	600	540	110	430	710	510	490	90	400	4	18,3	-----
8060-5010	800	600	600	500	100	710	510	550	480	70	4	17,5	-----
8060-5010T	800	600	600	500	100	710	510	550	480	70	4	18,1	Wheels
8060-2043	800	600	630	200	430	710	510	580	180	400	8	20,9	-----

CASE	EXTERIOR DIMENSIONS (mm)					INTERIOR DIMENSIONS (mm)					Handle (Pcs)	Weight (kg)	Special Features
	Length	Width	Height	Body Height	Lid Height	Length	Width	Height	Body Height	Lid Height			
8060-2043T	800	600	630	200	430	710	510	580	180	400	8	21,5	Wheels
8060-4023	800	600	630	400	230	710	510	580	380	200	4	19,2	-----
8060-4023T	800	600	630	400	230	710	510	580	380	200	4	19,8	Wheels
8060-3043	800	600	730	300	430	710	510	680	280	400	8	22,1	-----
8060-3043T	800	600	730	300	430	710	510	680	280	400	8	22,7	Wheels
8060-5023	800	600	730	500	230	710	510	680	480	200	4	20,2	-----
8060-5023T	800	600	730	500	230	710	510	680	480	200	4	20,8	Wheels
8060-4043	800	600	830	400	430	710	510	780	380	400	8	23,9	-----
8060-4043T	800	600	830	400	430	710	510	780	380	400	8	24,5	Wheels
8060-5043	800	600	930	500	430	710	510	880	480	400	8	24,9	-----
8060-5043T	800	600	930	500	430	710	510	880	480	400	8	25,5	Wheels
8070-2010	800	700	300	200	100	710	610	250	180	70	4	14,9	-----
8070-2010T	800	700	300	200	100	710	610	250	180	70	4	15,5	Wheels
8070-2022	800	700	420	200	220	710	610	370	180	190	4	17,0	-----
8070-2022T	800	700	420	200	220	710	610	370	180	190	4	17,6	Wheels
8070-4010	800	700	500	400	100	710	610	450	380	70	4	18,0	-----
8070-4010T	800	700	500	400	100	710	610	450	380	70	4	18,6	Wheels
8070-2042	800	700	620	200	420	710	610	570	180	390	8	21,4	-----
8070-2042T	800	700	620	200	420	710	610	570	180	390	8	22,0	Wheels
8070-4022	800	700	620	400	220	710	610	570	380	190	4	20,1	-----
8070-4022T	800	700	620	400	220	710	610	570	380	190	4	20,7	Wheels
8070-6010	800	700	700	600	100	710	610	650	580	70	4	21,5	-----
8070-6010T	800	700	700	600	100	710	610	650	580	70	4	22,1	Wheels
8070-2062	800	700	820	200	620	710	610	770	180	590	8	24,8	-----
8070-2062T	800	700	820	200	620	710	610	770	180	590	8	25,4	Wheels
8070-4042	800	700	820	400	420	710	610	770	380	390	8	24,5	-----
8070-4042T	800	700	820	400	420	710	610	770	380	390	8	25,1	Wheels
8070-6022	800	700	820	600	220	710	610	770	580	190	4	23,6	-----



R SERIES DIMENSIONS

CASE	EXTERIOR DIMENSIONS (mm)					INTERIOR DIMENSIONS (mm)					Handle (Pcs)	Weight (kg)	Special Features
	Length	Width	Height	Body Height	Lid Height	Length	Width	Height	Body Height	Lid Height			
8070-6022T	800	700	820	600	220	710	610	770	580	190	4	24,2	Wheels
8070-4062	800	700	1020	400	620	710	610	970	380	590	8	27,8	-----
8070-4062T	800	700	1020	400	620	710	610	970	380	590	8	28,4	Wheels
8070-6042	800	700	1020	600	420	710	610	970	580	390	8	28,0	-----
8070-6042T	800	700	1020	600	420	710	610	970	580	390	8	28,6	Wheels
8070-6062	800	700	1220	600	620	710	610	1170	580	590	8	31,3	-----
8070-6062T	800	700	1220	600	620	710	610	1170	580	590	8	31,9	Wheels
9040-3010	900	400	400	300	100	810	310	350	280	70	2	11,2	-----
9040-3010T	900	400	400	300	100	810	310	350	280	70	2	11,8	Wheels
9050-3010	900	500	400	300	100	810	410	350	280	70	2	12,5	-----
9050-3010T	900	500	400	300	100	810	410	350	280	70	2	13,1	Wheels
9050-3010TTEP	900	500	400	300	100	810	410	350	280	70	2	15,6	Wheels+Tepsi2
9050-4010	900	500	500	400	100	810	410	450	380	70	2	14,3	-----
9050-4010T	900	500	500	400	100	810	410	450	380	70	2	14,9	Wheels
9050-4010TTEP	900	500	500	400	100	810	410	450	380	70	2	17,4	Wheels+Tepsi2
9060-2010	900	600	300	200	100	810	510	250	180	70	4	14,6	-----
9060-2010T	900	600	300	200	100	810	510	250	180	70	4	15,2	Wheels
9060-3010	900	600	400	300	100	810	510	350	280	70	4	15,4	-----
9060-3010T	900	600	400	300	100	810	510	350	280	70	4	16,0	Wheels
9060-4010	900	600	500	400	100	810	510	450	380	70	4	17,9	-----
9060-4010T	900	600	500	400	100	810	510	450	380	70	4	18,5	Wheels
9060-5010	900	600	600	500	100	810	510	550	480	70	4	18,2	-----
9060-5010T	900	600	600	500	100	810	510	550	480	70	4	18,8	Wheels
9060-2043	900	600	630	200	430	810	510	580	180	400	8	22,7	-----
9060-2043T	900	600	630	200	430	810	510	580	180	400	8	23,3	Wheels
9060-3043	900	600	730	300	430	810	510	680	280	400	8	23,3	-----
9060-3043T	900	600	730	300	430	810	510	680	280	400	8	23,9	Wheels
9060-4043	900	600	830	400	430	810	510	780	380	400	8	26,0	-----

CASE	EXTERIOR DIMENSIONS (mm)					INTERIOR DIMENSIONS (mm)					Handle (Pcs)	Weight (kg)	Special Features
	Length	Width	Height	Body Height	Lid Height	Length	Width	Height	Body Height	Lid Height			
9060-4043T	900	600	830	400	430	810	510	780	380	400	8	26,6	Wheels
9060-5043	900	600	930	500	430	810	510	880	480	400	8	26,3	-----
9060-5043T	900	600	930	500	430	810	510	880	480	400	8	26,9	Wheels
9070-2010	900	700	300	200	100	810	610	250	180	70	4	16,2	-----
9070-2010T	900	700	300	200	100	810	610	250	180	70	4	16,8	Wheels
9070-2022	900	700	420	200	220	810	610	370	180	190	4	18,6	-----
9070-2022T	900	700	420	200	220	810	610	370	180	190	4	19,2	Wheels
9070-4010	900	700	500	400	100	810	610	450	380	70	4	19,7	-----
9070-4010T	900	700	500	400	100	810	610	450	380	70	4	20,3	Wheels
9070-2042	900	700	620	200	420	810	610	570	180	390	8	23,2	-----
9070-2042T	900	700	620	200	420	810	610	570	180	390	8	23,8	Wheels
9070-4022	900	700	620	400	220	810	610	570	380	190	4	22,1	-----
9070-4022T	900	700	620	400	220	810	610	570	380	190	4	22,7	Wheels
9070-6010	900	700	700	600	100	810	610	650	580	70	4	23,1	-----
9070-6010T	900	700	700	600	100	810	610	650	580	70	4	23,7	Wheels
9070-2062	900	700	820	200	620	810	610	770	180	590	8	26,7	-----
9070-2062T	900	700	820	200	620	810	610	770	180	590	8	27,3	Wheels
9070-4042	900	700	820	400	420	810	610	770	380	390	8	26,7	-----
9070-4042T	900	700	820	400	420	810	610	770	380	390	8	27,3	Wheels
9070-6022	900	700	820	600	220	810	610	770	580	190	4	25,5	-----
9070-6022T	900	700	820	600	220	810	610	770	580	190	4	26,1	Wheels
9070-4062	900	700	1020	400	620	810	610	970	380	590	8	30,2	-----
9070-4062T	900	700	1020	400	620	810	610	970	380	590	8	30,8	Wheels
9070-6042	900	700	1020	600	420	810	610	970	580	390	8	30,1	-----
9070-6042T	900	700	1020	600	420	810	610	970	580	390	8	30,7	Wheels
9070-6062	900	700	1220	600	620	810	610	1170	580	590	8	33,6	-----
9070-6062T	900	700	1220	600	620	810	610	1170	580	590	8	34,2	Wheels
10040-3010	1000	400	400	300	100	910	310	350	280	70	2	12,3	-----



R SERIES DIMENSIONS

CASE	EXTERIOR DIMENSIONS (mm)					INTERIOR DIMENSIONS (mm)					Handle (Pcs)	Weight (kg)	Special Features
	Length	Width	Height	Body Height	Lid Height	Length	Width	Height	Body Height	Lid Height			
10040-3010T	1000	400	400	300	100	910	310	350	280	70	2	12,9	Wheels
10050-3010	1000	500	400	300	100	910	410	350	280	70	2	13,7	-----
10050-3010T	1000	500	400	300	100	910	410	350	280	70	2	14,3	Wheels
10060-2010	1000	600	300	200	100	910	510	250	180	70	4	16,0	-----
10060-2010T	1000	600	300	200	100	910	510	250	180	70	4	16,6	Wheels
10060-3010	1000	600	400	300	100	910	510	350	280	70	4	17,2	-----
10060-3010T	1000	600	400	300	100	910	510	350	280	70	4	17,8	Wheels
10060-4010	1000	600	500	400	100	910	510	450	380	70	4	19,5	-----
10060-4010T	1000	600	500	400	100	910	510	450	380	70	4	20,1	Wheels
10060-5010	1000	600	600	500	100	910	510	550	480	70	4	20,4	-----
10060-5010T	1000	600	600	500	100	910	510	550	480	70	4	21,0	Wheels
10060-2043	1000	600	630	200	430	910	510	580	180	400	8	24,2	-----
10060-2043T	1000	600	630	200	430	910	510	580	180	400	8	24,8	Wheels
10060-3043	1000	600	730	300	430	910	510	680	280	400	8	25,4	-----
10060-3043T	1000	600	730	300	430	910	510	680	280	400	8	26,0	Wheels
10060-4043	1000	600	830	400	430	910	510	780	380	400	8	27,7	-----
10060-4043T	1000	600	830	400	430	910	510	780	380	400	8	28,3	Wheels
10060-5043	1000	600	930	500	430	910	510	880	480	400	8	28,4	-----
10060-5043T	1000	600	930	500	430	910	510	880	480	400	8	29,0	Wheels
10090-3013	1000	900	430	300	130	910	810	350	265	85	4	29,9	-----
10090-3013T	1000	900	430	300	130	910	810	350	265	85	4	30,5	Wheels
100100-3013	1000	1000	430	300	130	910	910	350	265	85	4	32,4	-----
100100-3013T	1000	1000	430	300	130	910	910	350	265	85	4	33,0	Wheels
11040-3010	1100	400	400	300	100	1010	310	350	280	70	2	13,4	-----
11040-3010T	1100	400	400	300	100	1010	310	350	280	70	2	14,0	Wheels
11050-3010	1100	500	400	300	100	1010	410	350	280	70	2	14,8	-----
11050-3010T	1100	500	400	300	100	1010	410	350	280	70	2	15,4	Wheels
11070-2015T	1100	700	350	200	150	1010	610	300	180	120	4	21,0	Wheels

CASE	EXTERIOR DIMENSIONS (mm)					INTERIOR DIMENSIONS (mm)					Handle (Pcs)	Weight (kg)	Special Features
	Length	Width	Height	Body Height	Lid Height	Length	Width	Height	Body Height	Lid Height			
11070-2025T	1100	700	450	200	250	1010	610	400	180	220	8	23,2	Wheels
11070-3615T	1100	700	510	360	150	1010	610	460	340	120	4	24,2	Wheels
11070-3625T	1100	700	610	360	250	1010	610	560	340	220	8	26,9	Wheels
11070-5215T	1100	700	670	520	150	1010	610	620	500	120	4	28,2	Wheels
11070-5225T	1100	700	770	520	250	1010	610	720	500	220	8	30,9	Wheels
12040-3010	1200	400	400	300	100	1110	310	350	280	70	2	14,5	-----
12040-3010T	1200	400	400	300	100	1110	310	350	280	70	2	15,1	Wheels
12050-3010	1200	500	400	300	100	1110	410	350	280	70	2	15,9	-----
12050-3010T	1200	500	400	300	100	1110	410	350	280	70	2	16,5	Wheels
12060-2010	1200	600	300	200	100	1110	510	250	180	70	4	18,8	-----
12060-2010T	1200	600	300	200	100	1110	510	250	180	70	4	19,4	Wheels
12060-3010F	1200	600	400	300	100	1110	510	250	180	70	4	20,5	Forklift Skids
12060-3010	1200	600	400	300	100	1110	510	350	280	70	4	19,1	-----
12060-3010T	1200	600	400	300	100	1110	510	350	280	70	4	19,7	Wheels
12060-3710TGR-M4-M16	1200	600	470								4	33,5	Wheels
12060-4010F	1200	600	500	400	100	1110	510	350	280	70	4	22,5	Forklift Skids
12060-4010	1200	600	500	400	100	1110	510	450	380	70	4	22,9	-----
12060-4010T	1200	600	500	400	100	1110	510	450	380	70	4	23,5	Wheels
12060-5010F	1200	600	600	500	100	1110	510	450	380	70	4	24,4	Forklift Skids
12060-5010	1200	600	600	500	100	1110	510	550	480	70	4	23,1	-----
12060-5010T	1200	600	600	500	100	1110	510	550	480	70	4	23,7	Wheels
12060-6010F	1200	600	700	600	100	1110	510	550	480	70	4	26,4	Forklift Skids
12060-2043	1200	600	630	200	430	1110	510	580	180	400	8	27,8	-----
12060-2043T	1200	600	630	200	430	1110	510	580	180	400	8	28,4	Wheels
12060-3043F	1200	600	730	300	430	1110	510	580	180	400	8	29,5	Forklift Skids
12060-3043	1200	600	730	300	430	1110	510	680	280	400	8	28,1	-----
12060-3043T	1200	600	730	300	430	1110	510	680	280	400	8	28,7	Wheels
12060-4043F	1200	600	830	400	430	1110	510	680	280	400	8	31,5	Forklift Skids



R SERIES DIMENSIONS

CASE	EXTERIOR DIMENSIONS (mm)					INTERIOR DIMENSIONS (mm)					Handle (Pcs)	Weight (kg)	Special Features
	Length	Width	Height	Body Height	Lid Height	Length	Width	Height	Body Height	Lid Height			
12060-4043	1200	600	830	400	430	1110	510	780	380	400	8	31,9	-----
12060-4043T	1200	600	830	400	430	1110	510	780	380	400	8	32,5	Wheels
12060-5043F	1200	600	930	500	430	1110	510	780	380	400	8	33,4	Forklift Skids
12060-5043	1200	600	930	500	430	1110	510	880	480	400	8	32,1	-----
12060-5043T	1200	600	930	500	430	1110	510	880	480	400	8	32,7	Wheels
12060-6043F	1200	600	1030	600	430	1110	510	880	480	400	8	35,4	Forklift Skids
12070-4010	1200	700	500	400	100	1110	610	450	380	70	4	24,9	-----
12070-4010T	1200	700	500	400	100	1110	610	450	380	70	4	25,5	Wheels
12070-6010	1200	700	700	600	100	1110	610	650	580	70	4	32,5	-----
12070-6010T	1200	700	700	600	100	1110	610	650	580	70	4	33,1	Wheels
14040-3010	1400	400	400	300	100	1310	310	350	280	70	2	16,4	-----
14040-3010T	1400	400	400	300	100	1310	310	350	280	70	2	17,0	Wheels
15060-3010	1500	600	400	300	100	1410	510	350	280	70	4	24,5	-----
15060-3010T	1500	600	400	300	100	1410	510	350	280	70	4	25,1	Wheels
15060-4010	1500	600	500	400	100	1410	510	450	380	70	4	26,8	-----
15060-4010T	1500	600	500	400	100	1410	510	450	380	70	4	27,4	Wheels
15060-5010	1500	600	600	500	100	1410	510	550	480	70	4	29,2	-----
15060-5010T	1500	600	600	500	100	1410	510	550	480	70	4	29,8	Wheels
160125-5144F	1600	1250	950	510	440	1510	1160	775	385	390	8	85,6	Forklift Skids
17040-3010	1700	400	400	300	100	1610	310	350	280	70	2	19,3	-----
17040-3010T	1700	400	400	300	100	1610	310	350	280	70	2	19,9	Wheels
18070-4010	1800	700	500	400	100	1710	610	450	380	70	4	35,4	-----
18070-4010T	1800	700	500	400	100	1710	610	450	380	70	4	36,0	Wheels
21060-5010F	2100	600	600	500	100	2010	510	445	375	70	4	39,7	Forklift Skids
22090-5852F	2200	900	1100	580	520	2110	810	910	445	465	8	100,3	Forklift Skids
28090-5852F	2800	900	1100	580	520	2710	810	910	445	465	8	123,2	Forklift Skids



CUSTOM SOLUTIONS



SHOCK AND VIBRATION DAMPENING

Delicate equipment and instruments are transported and used under complete protection from shock, vibration, moisture and impact.

Cases are furnished with the appropriate grade foam and/or shock mounting equipment in line with special project requirements.

As part of our manufacturing process all foam interiors are CAD designed and tailor made, in house, using high speed CNC routing, laminating, drilling, blocking and hand sculpting.

Suprobox R series liner foams are carefully selected to match the weight and shock/vibration requirements of the payload. Also, specific anti-static and conductive foams are used for static sensitive equipment when necessary.

Suprobox R series cases offer a complete service including design, manufacturing, customization and interior design.

Our Sales Team and Design engineers work together to create the perfect solution starting with the selection of the right case and right dampening material.



OPTIONS

Suprobox R Series cases come with stainless steel or heavy duty plated latches. Coupling catches and handles may be customized along with several other options such as color.

Cases are manufactured in two main colors: black and olive drab; while gray, desert mustard, blue, orange and red are offered as optional.

Pressure relief valve and Humidity indicator are main options. Others are hinged lid, tie down rings, padlockable catches and forklift skids.



Breather Valve



Membrane Valve



Humidity Indicator



Padlockable Catch



Hinged Lid



Tie Down Rings



Forklift Skids



Records Holder

COLOR OPTIONS



Black



Olive Drab



Gray



Blue



Desert Mustard



Orange




Red



SUPROBOX RACK SERIES

FEATURES

19" corrosion proof vertical square hole rack rails



Anti vibration mounts



M6 cage nuts



Easy grip



Built in edge casters (0812T range)



Multibrix stacking feature. Fits not only on all rack sizes but entire Suprobox range



Easy mount square punched inner frame



Lid hanger



Stainless steel catches



Flush mount easy grip ruggedized stainless steel handles



Manufactured as a solid uniform structure which makes it extra resistant to impact & vibration. UV resistant made to withstand extreme temperatures & solar load.





RACK03U48XR-0808 RACK03U48XR-0812T



CASE	U HEIGHT	EXTERIOR DIMENSIONS (mm)			INTERNAL CHASSIS DEPTH (mm)	WEIGHT (Kg)	HANDLE (Pcs)	WHEELS	PRESSURE VALVE
	U	Depth	Length	Width					
RACK03U48XR-0808	3U	285	776	570	480	15,7	4	No	Yes
RACK03U48XR-0812T	3U	285	806	570	480	16,9	6	Yes	Yes

RACK05U48XR-0808 RACK05U48XR-0812T



CASE	U HEIGHT	EXTERIOR DIMENSIONS (mm)			INTERNAL CHASSIS DEPTH (mm)	WEIGHT (Kg)	HANDLE (Pcs)	WHEELS	PRESSURE VALVE
	U	Depth	Length	Width					
RACK05U48XR-0808	5U	374	776	570	480	18,8	4	No	Yes
RACK05U48XR-0812T	5U	374	806	570	480	20,0	6	Yes	Yes

RACK07U48XR-0808 RACK07U48XR-0812T



CASE	U HEIGHT	EXTERIOR DIMENSIONS (mm)			INTERNAL CHASSIS DEPTH (mm)	WEIGHT (Kg)	HANDLE (Pcs)	WHEELS	PRESSURE VALVE
	U	Depth	Length	Width					
RACK07U48XR-0808	7U	463	776	570	480	20,7	4	No	Yes
RACK07U48XR-0812T	7U	463	806	570	480	22,0	6	Yes	Yes

RACK09U48XR-0808 RACK09U48XR-0812T



CASE	U HEIGHT	EXTERIOR DIMENSIONS (mm)			INTERNAL CHASSIS DEPTH (mm)	WEIGHT (Kg)	HANDLE (Pcs)	WHEELS	PRESSURE VALVE
	U	Depth	Length	Width					
RACK09U48XR-0808	9U	552	776	570	480	22,7	4	No	Yes
RACK09U48XR-0812T	9U	552	806	570	480	24,0	6	Yes	Yes

RACK11U48XR-0808 RACK11U48XR-0812T



CASE	U HEIGHT	EXTERIOR DIMENSIONS (mm)			INTERNAL CHASSIS DEPTH (mm)	WEIGHT (Kg)	HANDLE (Pcs)	WHEELS	PRESSURE VALVE
	U	Depth	Length	Width					
RACK11U48XR-0808	11U	641	776	570	480	25,7	4	No	Yes
RACK11U48XR-0812T	11U	641	806	570	480	27,1	6	Yes	Yes

RACK14U48XR-0808 RACK14U48XR-0812T



CASE	U HEIGHT	EXTERIOR DIMENSIONS (mm)			INTERNAL CHASSIS DEPTH (mm)	WEIGHT (Kg)	HANDLE (Pcs)	WHEELS	PRESSURE VALVE
	U	Depth	Length	Width					
RACK14U48XR-0808	14U	775	776	570	480	30,2	4	No	Yes
RACK14U48XR-0812T	14U	775	806	570	480	31,5	6	Yes	Yes

RACK03U61XR-0808 RACK03U61XR-0812T



CASE	U HEIGHT	EXTERIOR DIMENSIONS (mm)			INTERNAL CHASSIS DEPTH (mm)	WEIGHT (Kg)	HANDLE (Pcs)	WHEELS	PRESSURE VALVE
	U	Depth	Length	Width					
RACK03U61XR-0808	3U	285	900	570	610	17,9	4	No	Yes
RACK03U61XR-0812T	3U	285	930	570	610	19,1	6	Yes	Yes

RACK05U61XR-0808 RACK05U61XR-0812T



CASE	U HEIGHT	EXTERIOR DIMENSIONS (mm)			INTERNAL CHASSIS DEPTH (mm)	WEIGHT (Kg)	HANDLE (Pcs)	WHEELS	PRESSURE VALVE
	U	Depth	Length	Width					
RACK05U61XR-0808	5U	374	900	570	610	20,4	4	No	Yes
RACK05U61XR-0812T	5U	374	930	570	610	21,7	6	Yes	Yes

RACK07U61XR-0808 RACK07U61XR-0812T



CASE	U HEIGHT	EXTERIOR DIMENSIONS (mm)			INTERNAL CHASSIS DEPTH (mm)	WEIGHT (Kg)	HANDLE (Pcs)	WHEELS	PRESSURE VALVE
	U	Depth	Length	Width					
RACK07U61XR-0808	7U	463	900	570	610	22,5	4	No	Yes
RACK07U61XR-0812T	7U	463	930	570	610	23,8	6	Yes	Yes

RACK09U61XR-0808 RACK09U61XR-0812T



CASE	U HEIGHT	EXTERIOR DIMENSIONS (mm)			INTERNAL CHASSIS DEPTH (mm)	WEIGHT (Kg)	HANDLE (Pcs)	WHEELS	PRESSURE VALVE
	U	Depth	Length	Width					
RACK09U61XR-0808	9U	552	900	570	610	24,6	4	No	Yes
RACK09U61XR-0812T	9U	552	930	570	610	25,9	6	Yes	Yes

RACK11U61XR-0808 RACK11U61XR-0812T



CASE	U HEIGHT	EXTERIOR DIMENSIONS (mm)			INTERNAL CHASSIS DEPTH (mm)	WEIGHT (Kg)	HANDLE (Pcs)	WHEELS	PRESSURE VALVE
	U	Depth	Length	Width					
RACK11U61XR-0808	11U	641	900	570	610	27,3	4	No	Yes
RACK11U61XR-0812T	11U	641	930	570	610	28,7	6	Yes	Yes

RACK14U61XR-0808 RACK14U61XR-0812T



CASE	U HEIGHT	EXTERIOR DIMENSIONS (mm)			INTERNAL CHASSIS DEPTH (mm)	WEIGHT (Kg)	HANDLE (Pcs)	WHEELS	PRESSURE VALVE
	U	Depth	Length	Width					
RACK14U61XR-0808	14U	775	900	570	610	32,1	4	No	Yes
RACK14U61XR-0812T	14U	775	930	570	610	33,4	6	Yes	Yes

SUPROBOX RACKS



Shock and vibration protection for your electronics. Polymer case with aluminium rack frame suspended by anti-vibration mounts.

Available from 3U to 14U.

Tested to MIL-STD 810 and rated IP65.

All racks carry the Multibrix stacking feature.

Ideal for electronics, memory storage equipment, servers, lab and testing equipment, medical equipment, aerospace equipment, cameras and broadcasting equipment, meteorological equipment, flight simulators and mobile military equipment

- Ruggedized roto-molded case body made from impact resistant PE material
- 480 mm – 610 mm rack depth
- 80 mm or 120 mm lid with edge casters
- Standard 19" Rack width designed to meet ANSI/EIA-310-C
- Square hole rack rails to accommodate 6 mm standard cage nuts
- Black stainless steel heavy duty handles
- Shock mounts for maximum protection during transit
- Butterfly latches
- Metric holes for fastening your equipment.
- Watertight gasket
- Pressure relief valve (standard)
- Lid hangers (standard)

- Cable pouch (optional)
- Standard payload range 40 to 150 lbs
- Size range 3U to 14U
- Light Weight compact design
- Gridlines featured on the lid are specially designed for pallet strapping.
- Reduced Footprint
- Multibrix® stacking and storage system (secure stacking and cross stacking of same or different size cases).
- Tested and Approved - MIL-STD 810 G
- IP 65 rated for dust and water ingress



SUPROBOX Rack - 480 mm Chassis

Part Code	U Height	External Dimension (mm)			Chassis Depth	Weight	Handles	Wheels	Pressure Valve
	U	Height	Length	Width	mm	Kg	Pcs		
RACK03U48XR-0808	3U	285	776	570	480	15,7	4	No	Yes
RACK03U48XR-0812T	3U	285	806	570	480	16,9	6	Yes	Yes
RACK05U48XR-0808	5U	374	776	570	480	18,8	4	No	Yes
RACK05U48XR-0812T	5U	374	806	570	480	20,0	6	Yes	Yes
RACK07U48XR-0808	7U	463	776	570	480	20,7	4	No	Yes
RACK07U48XR-0812T	7U	463	806	570	480	22,0	6	Yes	Yes
RACK09U48XR-0808	9U	552	776	570	480	22,7	4	No	Yes
RACK09U48XR-0812T	9U	552	806	570	480	24,0	6	Yes	Yes
RACK11U48XR-0808	11U	641	776	570	480	25,7	4	No	Yes
RACK11U48XR-0812T	11U	641	806	570	480	27,1	6	Yes	Yes
RACK14U48XR-0808	14U	775	776	570	480	30,2	4	No	Yes
RACK14U48XR-0812T	14U	775	806	570	480	31,5	6	Yes	Yes

SUPROBOX Rack - 610 mm Chassis

Part Code	U Height	External Dimension (mm)			Chassis Depth	Weight	Handles	Wheels	Pressure Valve
	U	Height	Length	Width	mm	Kg	Pcs		
RACK03U61XR-0808	3U	285	900	570	610	17,9	4	No	Yes
RACK03U61XR-0812T	3U	285	930	570	610	19,1	6	Yes	Yes
RACK05U61XR-0808	5U	374	900	570	610	20,4	4	No	Yes
RACK05U61XR-0812T	5U	374	930	570	610	21,7	6	Yes	Yes
RACK07U61XR-0808	7U	463	900	570	610	22,5	4	No	Yes
RACK07U61XR-0812T	7U	463	930	570	610	23,8	6	Yes	Yes
RACK09U61XR-0808	9U	552	900	570	610	24,6	4	No	Yes
RACK09U61XR-0812T	9U	552	930	570	610	25,9	6	Yes	Yes
RACK11U61XR-0808	11U	641	900	570	610	27,3	4	No	Yes
RACK11U61XR-0812T	11U	641	930	570	610	28,7	6	Yes	Yes
RACK14U61XR-0808	14U	775	900	570	610	32,1	4	No	Yes
RACK14U61XR-0812T	14U	775	930	570	610	33,4	6	Yes	Yes





Multibrix Stacking System

Multibrix® is a patented unique stacking and storage system allowing secure stacking and cross stacking of same or different size cases.

Two different size Suprobox cases featuring the **Multibrix®** stacking and storage system can easily interlock so they can be stacked securely.


The same system allows the cases to be stacked at a 90° angle and transported as thus, as an extra space saving option.

The **Multibrix®** stacking feature is designed to enhance the structural rigidity of the cases.

Gridlines featured on the lid are specially designed for pallet strapping.

The Suprobox range comes in multiples of 10 cm sizes which makes them perfect for standard palletizing and metric packaging options.







TESTED AND APPROVED

MIL-STD-810 G

VIBRATION

MIL STD 810G Method 514.6 Procedure I Category 4

FUNCTIONAL SHOCK

MIL STD 810G Method 516.6 Procedure I

TRANSIT DROP

using MIL STD 810G Method 516.6 Procedure IV

LOW TEMPERATURE

MIL STD 810G Method 502.5 Procedure

HIGH TEMPERATURE

MIL STD 810G Method 501.5 Procedure I

HUMIDITY

MIL STD 810G Method 507.5 Procedure II

BLOWING SAND

MIL STD 810G Method 510.5 Procedure II

BLOWING RAIN

MIL STD 810G Method 506.5

IP RATING

IP 65 / IP 67 EN 60529



NBCSYSTEM
SISTEMI DI PROTEZIONE

NBC SYSTEM SRL

Località Ponte di Cetti - Km 76,100 - VITERBO 01100 -VT- Italy

Tel+39 0761.470427 Mail: info@nbcsystem.it

www.nbcsystem.it